CERTIFICATE OF COMPLIANCE

Certificate Number 20170102-EX15835

Report Reference EX15835-20130329

Issue Date 2017-JANUARY-02

Issued to: HD FIRE PROTECT PVT LTD

K-98, MIDC AJANTA RD

JALGAON MH 425003 INDIA

This is to certify that representative samples of

PROPORTIONERS, FOAM CONCENTRATE

"See Addendum Page"

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 162 - UL Standard For Safety For Foam Equipment and

Liquid Concentrates

Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC





CERTIFICATE OF COMPLIANCE

 Certificate Number
 20170102-EX15835

 Report Reference
 EX15835-20130329

 Issue Date
 2017-JANUARY-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

36 to 3963 gal capacity ASME for horizontal installation. 36 to 1982 gal capacity ASME for vertical installation. Models RCF-B,-S and RCW-B,-S ratio flow controllers in sizes 2-1/2, 3, 4, 6 and 8 ln.

Following are the equivalent length values for the controllers based on a roughness factor of 130 and Schedule 40 steel pipe:

Controller Size In.	Equivalent Length Ft
2-1/2	38.2
3	21.8
4	16.7
6	30.1
8	55.3

Models RCW-BM, -SM, and RCF-BM,-SM ratio flow controllers in the 2-1/2 In. and 6 In. size.

Following are the equivalent length values for the controllers based on a roughness factor of 130 and Schedule 40 steel pipe:

Controller Size In.	Equivalent Length Ft
2-1/2	357.2
6	48.9



Bruce Mahrenholz, Director North American Certification Program

UL LLC



