

CERTIFICATE OF COMPLIANCE

Certificate Number 20130109-EX16058
Report Reference EX16058-20120629
Issue Date 2013-JANUARY-09


Issued to: HD FIRE PROTECT PVT LTD
K-98, MIDC
AJANTA RD
JALGAON MH 425003 INDIA

This is to certify that representative samples of FOAM-DISCHARGE OUTLETS
“See Next Page For Models”

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 162 - Foam Equipment and Liquid Concentrates
Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing Mark should be considered as being covered by UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word “LISTED”; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20130109-EX16058
Report Reference EX16058-20120629
Issue Date 2013-JANUARY-09

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Foam Chamber Models FCA 65, FCA-S 65, FCA 80, FCA-S 80, FCA 100, FCA-S 100, RPA 65, RPA-S 65 of sizes 2-1/2, 2-1/2, 3, 3, 4, 4, 2-1/2 and 2-1/2 inches respectively.

Foam Makers Models FMA 50, FMA-S 50, FMA 65, FMA-S 65, FMB 50, FMB-S 50, FMB 65, FMB-S 65 of sizes 2, 2 2-1/2, 2-1/2, 2, 2, 2-1/2 & 2-1/2 inches respectively.
FMA 50 & FMA 65 shall be used with discharge device, FP.
FMA-S 50 & FMA-S 65 shall be used with discharge device, FP-S.
FMB 50 & FMB 65 shall be used with discharge device, FD & SD.
FMB-S 50 & FMB-S 65 shall be used with discharge device, FD-S & SD-S.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

