

CERTIFICATE OF COMPLIANCE

Certificate Number 20161206-EX5056
Report Reference EX5056-19961001
Issue Date 2016-DECEMBER-06

Issued to: HD FIRE PROTECT PVT LTD
D-6/2, Road No. 34
Wagle Industrial Estate
Thane Maharashtra 400604 INDIA

This is to certify that representative samples of NOZZLES, SPRAY TYPE, FIXED
See Addendum

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: ANSI/UL 2351, Spray Nozzles for Fire-Protection Service
Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20161206-EX5056
Report Reference EX5056-19961001
Issue Date 2016-DECEMBER-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Medium velocity (MV) non-automatic fixed spray nozzle, Model A and E in the sizes Km-18, Km-22, Km-30, Km-35, Km-41, Km-51, Km-64, Km-79, Km-91 and Km-102 K-factors. and Model MV-AS (with strainer) in the Km-18, Km-22, Km-30, Km-35 and Km-41 K-factors and with various deflector designs to produce spray angles of 65, 80, 90, 100, 110, 120 and 140 degrees.

High velocity non-automatic pattern spray nozzles, Model HV-A and Model HV-B (without strainer) Model HV-AS and Model HV-BS (with strainer) in the following sizes and spray angles: Km-18 (800), Km-22 (750), Km-23 (1200), Km-26 (1000), Km-32 (900) and Km-42 (1150).

Medium velocity (MV) non-automatic fixed spray nozzle, Model MV-B with Km-18, Km-22, Km-30, Km-35, Km-41, Km-51, Km-64, Km-79, Km-91 and Km-102 K-factors and Model MV-BS (with strainer) with Km-18, Km-22, Km-30, Km-35 and Km-41 K-factors and with various deflector designs to produce spray angles of 65, 80, 90, 100, 110, 120 and 140 degrees.

Models HV-H and HV-HB non-automatic spray nozzles with, Km-48, Km-58, Km-61 and Km-78 metric K-factors.

Model MV-C, MV-CB and MV-CE are Medium velocity reverse action water spray nozzle with Km-30, Km-51, Km-64, Km-79 and Km-120 each in spray angle of 140 and 120 degree.

Model MV-CS and MV-CBS are Medium velocity reverse action water spray nozzle with Km-18, Km-22 each in spray angle of 120 and 140 degree.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

